



The diagram illustrates a ditch cross-section with the following dimensions and labels:

- Pochylenie skarp** (Slope of the bank) and **Wysokość skarp** (Height of the bank) are indicated for the right-hand slope.
- Nasyp** (Fill) is labeled for the top right section.
- Wykop** (Excavation) is labeled for the bottom left section.
- Wyrównanie (powyżej minimalnych 5 cm)** (Leveling (above minimum 5 cm)) is labeled for the bottom right section.
- Frezowanie** (Milling) is labeled for the bottom left section.
- Dimensions shown include $L=20m$ for the bottom left section, $L=10m$ for the bottom right section, and $L=10m$ for the top right section.

Rogrowiec

Biuro Usług Projektowych

20-150 Lublin, ul. M. Rogackiego 19
 ☎ (81) 469 15 45
biuro@rogrowiec.info
www.rogrowiec.info
 NIP: 712-128-29-23 REGON: 43991788

Krasnostawski
 drog. 22-000 Krasnostaw w Krasnymstawie
 owa 6, 22-300 Krasnostaw

podkowa drogi powiatowej nr 3114L,
 pułki – Piaski Szlacheckie – Izłbica
 0+000 do km 0+980 o dł. 0,980 km

czekroje poprzeczne

Imię i nazwisko	Podpisa	Podpiszemy 2020 r.
BRANZA DROGOWA		Skala: 1:100
mgr inż. Robert Pulinski		Nr usay: 9/PN/20
pr. bud. Nr U1B/0077/0003/03		Nr rys: 5/1
mgr inż. Paweł Surka		